

# ZR25K5-TF5

HCFC, R-22, 60Hz, 3- Phase, 200/230 V

Air Conditioning



**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

## Performance

Evap(°F)/Cond(°F)	45 / 130	50 / 100
RG(°F)/Liq(°F)	65.0 / 115.0	70.0 / 85.0
Capacity (Btu/hr)	25300	32800
Power (Watts):	2320	1555
Current (Amps):	6.85	5.15
EER (Btu/Wh):	10.90	21.10
Mass Flow (lbs/hr):	371	420
Sound Power (dBA):	68 Avg	73 Max
Vibration (mils(peak-peak)):	2.0 Avg	3.0 Max
Record Date:	2010-11-16	

## Mechanical

Number of Cylinders:	0	Displ(in <sup>3</sup> /Rev):	2.08
Bore Size(in):	0.00	Displ(ft <sup>3</sup> /hr):	252.66
Stroke(in):	0.00		
Overall Length (in):	9.50	Mounting Length (in):	7.50
Overall Width (in):	9.50	Mounting Width (in):	7.50
Overall Height (in):	15.86	Mounting Height (in):	16.08 *
Suction Size (in):	3/4 Stub		
Discharge Size (in):	1/2 Stub		
Oil Recharge (oz):	19		
Initial Oil Charge (oz):	25		
Net Weight (lbs):	49.1		
Internal Free Volume (in <sup>3</sup> ):	122.8		
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

## Electrical

LRA-High*:	58.0	MCC (Amps):	12.5	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	
LRA Low*:		Max Operating Current:	9.0		
RLA(=MCC/1.4;use for contactor selection):	8.9				
RLA(=MCC/1.56;use for breaker & wire size selection):	8				
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

## Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	50	3	200/220	Air Conditioning