

N2NL-0200-TAC-300

CFC, R-502, 60Hz, 3- Phase, 208/230 V



Availability : **Obsolete**

Mechanical

Unit Height (in):	21.4
Unit Length (in):	24.0
Unit Width (in):	20.2
Ship Weight (lbs):	250.0
Condensor Type:	
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 F
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	0.500
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	MIN
Oil Recharge Amount (oz):	60

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	9.0
Compressor:	EAV1-0200-TAC-100
Compressor LRA - Low:	
Compressor LRA - High:	46.0
Compressor LRA - Half winding:	
Compressor RLA:	6.6
UL:	None
UL File #:	None
UL Guide Card:	None
Amps Per Motor:	0.3
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	07-May-2004	Return Gas Temp. (°F):	65
Compressor:	EAV1-0200-TAC-100 x 1	Subcooling (°F):	5
Performance No:	7577	Air Flow Rate (CFM)	0