

MBFH-0050-IAA-272

CFC, R-12, 60Hz, 1- Phase, 115 V



Availability : Custom US OEM Or Wholesaler

Mechanical

Unit Height (in):	11.7
Unit Length (in):	16.3
Unit Width (in):	13.1
Ship Weight (lbs):	51.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	1/4 S
Suction Connection Size (in)/Type:	1/2 S
Discharge Line Size(in):	0.250
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	ABO
Oil Recharge Amount (oz):	24

Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	13.8
Compressor:	ART62C1-IAA-103
Compressor LRA - Low:	
Compressor LRA - High:	51.00
Compressor LRA - Half winding:	
Compressor RLA:	10.30
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
Amps Per Motor:	0.53
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	20-Jul-2002	Return Gas Temp. (°F):	65	
Compressor:	ART62C1-IAA-103 x 1	Subcooling (°F):	5	
Performance No:	3905	Air Flow Rate (CFM)	300	
90°F Ambient Air Temperature				
<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
45	5,330	128.3	38.3	6.0