

FJWL-C200-TFC-020

HFC, R-404A, 60Hz, 3- Phase, 208/230 V

Availability : **Standard US Wholesaler**

Mechanical

Unit Height (in):	14.6
Unit Length (in):	24.0
Unit Width (in):	16.4
Ship Weight (lbs):	112.0
Condensor Type:	Water
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	0.38
Water Inlet (in):	0
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	45

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	9.3
Compressor:	CF06K6E-TF5-295
Compressor LRA - Low:	
Compressor LRA - High:	52.0
Compressor LRA -	
Compressor RLA:	7.0
Elect Application	1
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	0.27
Fan Motor Quantity:	1.00

Water- Cooled Unit Performance

Release Date:	09-Oct-2002	Return Gas Temp. (°F):	40
Compressor:	CF06K6E-TF5-295 x 1	Subcooling (°F):	5
Performance No:	5992	Condenser Water Inlet Temp.(°F)	75.0
		Water Temp Diff.(°F)	20

105°F Condensing Temperature			
Evap Temp	Unit Capacity	Cond Water	
(°F)	(Btu/hr)	(gal/min)	(psi)
-30	3,940	0.7	0.2
-25	5,020	0.8	0.3
-20	6,250	1.0	0.3
-15	7,620	1.2	0.4
-10	9,090	1.4	0.6
-5	10,700	1.5	0.7
0	12,300	1.7	0.9