

CR18K6E-PFV

HCFC, R-22, 60Hz, 1- Phase, 208/230 V

UL High Temp

Production Status:



Performance

| | | |
|------------------------------|----------|----------|
| Evap(°F)/Cond(°F) | 45 / 130 | 45 / 100 |
| Capacity (Btu/hr) | 17000 | 23900 |
| Power (Watts): | 1585 | 1344 |
| Current (Amps): | | |
| EER (Btu/Wh): | 10.73 | 17.78 |
| Mass Flow (lbs/hr): | | |
| Sound Power (dBA): | 71 Avg | 76 Max |
| Vibration (mils(peak-peak)): | 1.6 Avg | 2.6 Max |
| Record Date: | | |

Mechanical

| | | | |
|---|-------|------------------------------|---------|
| Number of Cylinders: | 2 | Displ(in ³ /Rev): | 1.87 |
| Bore Size(in): | 1.52 | Displ(ft ³ /hr): | 226.82 |
| Stroke(in): | 0.52 | | |
| Overall Length (in): | 10.23 | Mounting Length (in): | 7.50 |
| Overall Width (in): | 9.65 | Mounting Width (in): | 7.50 |
| Overall Height (in): | 13.19 | Mounting Height (in): | 13.56 * |
| Suction Size (in): | | 3/4 Stub | |
| Discharge Size (in): | | 1/2 Stub | |
| Oil Recharge (oz): | | 43 | |
| Initial Oil Charge (oz): | | 45 | |
| Net Weight (lbs): | | 61 | |
| Internal Free Volume (in ³): | | | |
| Horse Power: | | | |
| *Overall compressor height on Copeland Brand Product's specified mounting grommets. | | | |

Electrical

| | | | | | |
|---|-------------|------------------------|----------|---------------|------------------|
| LRA-High*: | 49.0 | MCC (Amps): | 14.6 | UL File No: | |
| LRA-Half Winding: | | RPM: | | UL File Date: | 28-Dec-1984 |
| LRA Low*: | | Max Operating Current: | | | |
| RLA(=MCC/1.4;use for contactor selection): | | 10.4 | | | |
| RLA(=MCC/1.56;use for breaker & wire size selection): | | 9.4 | | | |
| *Low and High refer to the low and high nominal voltage ranges for which the motor is approved. | | | | | |
| Type | Part No | Low MFD | High MFD | Volts | User Description |
| Start Capacitor | 014-0061-16 | 43.0 | 52.0 | 330 | LOW TORQUE |
| Start Capacitor | 014-0061-28 | 145.0 | 175.0 | 250 | HIGH TORQUE |
| Run Capacitor | 014-0064-05 | 25.0 | 0.0 | 370 | |

Alternate Applications

| Refrigerant | Freq (Hz) | Phase | Voltage | Application |
|-------------|-----------|-------|---------|------------------|
| R-22 HCFC | 50 | 1 | 200 | UL High Temp |
| R-407C HFC | 50 | 1 | 200 | Air Conditioning |
| R-407C HFC | 60 | 1 | 208/230 | Air Conditioning |
| R-407C HFC | 50 | 1 | 200 | UL High Temp |