


CATCH-ALL REPLACEABLE CORE TYPE



Catch-All THE PERFECT FILTER-DRIER

The rugged construction of the Replaceable Core Catch-All has proven itself in the field for many years. The design features include:

1. The famous **molded porous core** for maximum contaminant removal. The core cannot swell, powder, or pack—assuring ease of installation and removal;
2. The **bolt and nut attachment** of the end plate provides simple and trouble free installation;
3. The **internal** construction gives a one piece assembly and assures proper core alignment;
4. A **complete line** of fitting sizes —all with copper fittings;
5. **No plastic parts** are used —all internal parts are plated steel;
6. A **corrosion resistant powder paint** protects the exterior of the shell.

REPLACEABLE CORE TYPE

| TYPE | CONNECTIONS (in) ODF Solder | NUMBER OF CORES | CORE PART NO | VOLUME OF DESICCANT (cu in) | MOUNTING BRACKETS | OVERALL LENGTH (in) |
|----------------------|--------------------------------|--------------------|-----------------------------------|--------------------------------|----------------------|------------------------|
| C-485,C-485-G | 5/8 | 1 | RCW-48, RC-4864, or RC-4864-HH | 48 | A-685 | 9.15 |
| C-485-T | 5/8 | 1 | RCW-48, RC-4864, or RC-4864-HH | 48 | A-685 | 9.15 |
| C-487,C-487-G | 7/8 | 1 | RCW-48, RC-4864, or RC-4864-HH | 48 | A-685 | 9.30 |
| C-487-T | 7/8 | 1 | RCW-48, RC-4864, or RC-4864-HH | 48 | A-685 | 9.30 |
| C-489-T,C-489-G | 1-1/8 | 1 | RCW-48, RC-4864, or RC-4864-HH | 48 | A-685 | 9.50 |
| C-4811-T,C-4811-G | 1-3/8 | 1 | RCW-48, RC-4864, or RC-4864-HH | 48 | A-685 | 9.60 |
| C-4813-T,C-4813-G | 1-5/8 | 1 | RCW-48, RC-4864, or RC-4864-HH | 48 | A-685 | 9.60 |
| C-967,C-967-G | 7/8 | 2 | RCW-48, RC-4864, or RC-4864-HH | 96 | A-685 | 14.84 |
| C-967-T | 7/8 | 2 | RCW-48, RC-4864, or RC-4864-HH | 96 | A-685 | 14.84 |
| C-969,C-969-G | 1-1/8 | 2 | RCW-48, RC-4864, or RC-4864-HH | 96 | A-685 | 15.04 |
| C-969-T | 1-1/8 | 2 | RCW-48, RC-4864, or RC-4864-HH | 96 | A-685 | 15.04 |
| C-9611-T,C-9611-G | 1-3/8 | 2 | RCW-48, RC-4864, or RC-4864-HH | 96 | A-685 | 15.14 |
| C-9613-T,C-9613-G | 1-5/8 | 2 | RCW-48, RC-4864, or RC-4864-HH | 96 | A-685 | 15.14 |
| C-1449,C-1449-G | 1-1/8 | 3 | RCW-48, RC-4864, or RC-4864-HH | 144 | A-685 | 20.58 |
| C-1449-T | 1-1/8 | 3 | RCW-48, RC-4864, or RC-4864-HH | 144 | A-685 | 20.58 |
| C-14411,C-14411-G | 1-3/8 | 3 | RCW-48, RC-4864, or RC-4864-HH | 144 | A-685 | 20.68 |
| C-14411-T | 1-3/8 | 3 | RCW-48, RC-4864, or RC-4864-HH | 144 | A-685 | 20.68 |
| C-14413-T,C-14413-G | 1-5/8 | 3 | RCW-48, RC-4864, or RC-4864-HH | 144 | A-685 | 20.68 |
| C-19211,C-19211-G | 1-3/8 | 4 | RCW-48, RC-4864, or RC-4864-HH | 192 | A-685 | 26.22 |
| C-19211-T | 1-3/8 | 4 | RCW-48, RC-4864, or RC-4864-HH | 192 | A-685 | 26.22 |
| C-19213,C-19213-G | 1-5/8 | 4 | RCW-48, RC-4864, or RC-4864-HH | 192 | A-685 | 26.22 |
| C-19213-T | 1-5/8 | 4 | RCW-48, RC-4864, or RC-4864-HH | 192 | A-685 | 26.22 |
| C-30013,C-30013-G | 1-5/8 | 3 | RCW-100, RC-10098, or RC-10098-HH | 300 | A-175-2 | 26.22 |
| C-30013-T | 1-5/8 | 3 | RCW-100, RC-10098, or RC-10098-HH | 300 | A-175-2 | 27.94 |
| C-30017-T,C-30017-G | 2-1/8 | 3 | RCW-100, RC-10098, or RC-10098-HH | 300 | A-175-2 | 28.06 |
| C-40017,C-40017-G | 2-1/8 | 4 | RCW-100, RC-10098, or RC-10098-HH | 400 | A-175-2 | 28.06 |
| C-40017-T | 2-1/8 | 4 | RCW-100, RC-10098, or RC-10098-HH | 400 | A-175-2 | 34.56 |
| C-40021-T,C-40021-G | 2-5/8 | 4 | RCW-100, RC-10098, or RC-10098-HH | 400 | A-175-2 | 34.57 |
| C-40025-T,C-40025-G | 3-1/8 | 4 | RCW-100, RC-10098, or RC-10098-HH | 400 | A-175-2 | 34.44 |
| C-40029-T,C-40029-G | 3-5/8 | 4 | RCW-100, RC-10098, or RC-10098-HH | 400 | A-175-2 | 34.81 |
| C-40033-T,-C-40033-G | 4-1/8 | 4 | RCW-100, RC-10098, or RC-10098-HH | 400 | A-175-2 | 35.12 |

OPTIONAL SECONDARY FILTER – ORDER SEPARATELY

| Filter Part No. | Description | Quantity Required |
|---|-------------------------------|-------------------|
| FS-480 FS-960 FS-1440 FS-19200 | Filter for C-480 Series Shell | 1 |