

# 8DS1R67M0-TSK

HCFC, R-22, 60Hz, 3- Phase, 208/230 V

Air Conditioning



**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

## Performance

Evap(°F)/Cond(°F)	45 / 130	35 / 105
RG(°F)/Liq(°F)	65.0 / 115.0	55.0 / 90.0
Capacity (Btu/hr)	644000	637000
Power (Watts):	63400	51100
Current (Amps):	199.70	167.70
EER (Btu/Wh):	10.20	12.50
Mass Flow (lbs/hr):	9450	8450
Sound Power (dBA):	0 Avg	0 Max
Vibration (mils(peak-peak)):	0.0 Avg	0.0 Max
Record Date:	2006-08-22	

## Mechanical

Number of Cylinders:	8	Displ(in <sup>3</sup> /Rev):	126.42
Bore Size(in):	2.94	Displ(ft <sup>3</sup> /hr):	7681.73
Stroke(in):	2.33		
Overall Length (in):	32.81	Mounting Length (in):	18.00
Overall Width (in):	21.41	Mounting Width (in):	12.00
Overall Height (in):	22.97	Mounting Height (in):	24.66 *
Suction Size (in):	3 1/8 Sweat		
Discharge Size (in):	1 5/8 Sweat		
Oil Recharge (oz):	250		
Initial Oil Charge (oz):	260		
Net Weight (lbs):	850		
Internal Free Volume (in <sup>3</sup> ):			
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

## Electrical

LRA-High*:	1070	MCC (Amps):	314.0	UL File No:	SA-2337
LRA-Half Winding:	654	RPM:	3500	UL File Date:	01-Oct-1982
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):		224.3			
RLA(=MCC/1.56;use for breaker & wire size selection):		201.3			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

## Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	50	3	200	
R-502 CFC	50	3	200	
R-22 HCFC	50	3	400	
R-502 CFC	50	3	400	
R-22 HCFC	60	3	460	Air Conditioning
R-502 CFC	60	3	460	Medium Temperature
R-502 CFC	60	3	208/230	Medium Temperature