

XJAL-035Z-CFV-022

HFC, R-404A, 60Hz, 1- Phase, 208/230 V



Availability : Standard US Wholesaler

Mechanical

Unit Height (in):	
Unit Length (in):	
Unit Width (in):	
Ship Weight (lbs):	98.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	null null
Suction Connection Size (in)/Type:	null null
Discharge Line Size(in):	
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	3MA
Oil Recharge Amount (oz):	46

Electrical

Max Fuse Size:	50
Min Circuit Ampacity:	30.7
Compressor:	ZXI11KCE-PFV-647
Compressor LRA - Low:	
Compressor LRA - High:	137.0
Compressor LRA - Half winding:	
Compressor RLA:	26.4
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	10-Jun-2009	Return Gas Temp. (°F):	65
Compressor:	ZXI11KCE-PFV-647 x 1	Subcooling (°F):	0
Performance No:	7913	Air Flow Rate (CFM)	2050

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-40	9,700	99.9	9.9	3.6
-35	11,100	100.8	10.8	4.0
-30	12,600	101.7	11.7	4.4
-25	14,200	102.7	12.7	4.9
-20	15,900	103.8	13.8	5.3
-15	17,700	105.1	15.1	5.7
-10	19,700	106.3	16.3	6.1
-5	21,700	107.7	17.7	6.5
0	23,900	109.2	19.2	6.9