



Klixon Pressure Switches

MARS SERIES **333**

COMPONENT

KLIXON



43337

Fixed Setting Pressure Controls High Pressure Cut-Outs

MARS offers the most complete line of high pressure cut-outs available.

Specifications:

- Contacts rated at 6 amps, 24-240 volts
- 1/4" female flare S.A.E. mounting
- 18" leads

Features:

- Tamper proof construction
- Direct mounting on tubing
- UL & CSA recognized

The 4 - Series Klixon Pressure Switches. This newest set of designs delivers the reliability and performance that has made Klixon the most trusted name in the electromechanical sensor business. The 4 - Series line of pressure switches covers many new R410A applications along with traditional pressure setting switches.

Klixon Brand, UL and CUL, Compact size, light weight for direct mounting, Factory Set, Hermetically Sealed Sensor.

5.8 FLA - 34.8 LRA @ 120 VAC, 2.9 FLA - 15.0 LRA @ 240 VAC, 100,000 Cycle Life at Rated Current.

High Pressure Cut-Out - Open on Pressure Rise, Automatic Reset, Normally Closed

3 SERIES MARS NO.	4 SERIES MARS NO.	CUT OUT	CUT IN	NOTES
33353	43337	200	150	1/4" Female Flare S.A.E. Mounting
	43321	225	150	1/4" Female Flare S.A.E. Mounting
33354	43322	250	150	1/4" Female Flare S.A.E. Mounting
33310	43324	275	195	1/4" Female Flare S.A.E. Mounting
33355	43325	300	200	1/4" Female Flare S.A.E. Mounting
33313	43326	325	225	1/4" Female Flare S.A.E. Mounting
33316	43320	350	245	1/4" Female Flare S.A.E. Mounting
33356	43327	350	250	1/4" Female Flare S.A.E. Mounting
33319	43328	375	275	1/4" Female Flare S.A.E. Mounting
33357	43329	400	200	1/4" Female Flare S.A.E. Mounting
33322	43330	400	280	1/4" Female Flare S.A.E. Mounting
33370	43340	400	300	1/4" Female Flare S.A.E. Mounting w/24" leads (1 stripped, 1 w/1/4" female flag QC)
33358	43331	400	300	1/4" Female Flare S.A.E. Mounting w/24" leads (1 stripped, 1 w/1/4" female flag QC)
33365 ¹	43313 ¹	410	290	1/4" Female Flare S.A.E. Mounting
33325	43332	425	300	1/4" Female Flare S.A.E. Mounting
	43333	425	325	1/4" Female Flare S.A.E. Mounting
33359	43334	450	250	1/4" Female Flare S.A.E. Mounting
	43365	590	418	1/4" Female Flare w/snubber
33361	43335	600	475	1/4" Female Flare S.A.E. Mounting
	43366	610	420	1/4" Copper Clad SS Tube, 90 degree elbow w/snubber
	43376	610	420	1/4" Copper Clad SS Tube w/snubber
33369	43339	630	480	1/4" Female Flare S.A.E. Mounting
	43367	650	450	1/4" Copper Clad SS Tube w/snubber

¹ Manual reset