

# M4CL-0034-IAA-149

HFC, R-404A, 60Hz, 1- Phase, 115 V



**Availability :** Custom US OEM Or Wholesaler

## Mechanical

Unit Height (in):	
Unit Length (in):	
Unit Width (in):	
Ship Weight (lbs):	55.0
Condensor Type:	
CopeVap Water Storage:	
Liquid Connection Size (in)/Type:	null null
Suction Connection Size (in)/Type:	null null
Discharge Line Size(in):	
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	12

## Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	7.9
Compressor:	AFE11C3E-IAA-103
Compressor LRA - Low:	
Compressor LRA - High:	29.00
Compressor LRA - Half winding:	
Compressor RLA:	5.60
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
Amps Per Motor:	0.53
Fan Motor Quantity:	1

## Air - Cooled Unit Performance

Release Date:	23-Apr-2007	Return Gas Temp. (°F):	40
Compressor:	AFE11C3E-IAA-103 x 1	Subcooling (°F):	5
Performance No:	7796	Air Flow Rate (CFM)	330

### 90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-25	870	98.9	8.9	2.4
-20	1,050	99.9	9.9	2.8
-15	1,240	100.9	10.9	3.1
-10	1,430	101.9	11.9	3.3
-5	1,640	103.0	13.0	3.6
0	1,850	104.4	14.4	3.9