

WJWL-0151-TAC-001

HFC, R-404A, 60Hz, 3- Phase, 208/230 V

Availability : Custom US OEM Or Wholesaler

Mechanical

Unit Height (in):	17.0
Unit Length (in):	34.8
Unit Width (in):	14.5
Ship Weight (lbs):	214.0
Condensor Type:	Water
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 F
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	0.50
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	22

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	8.3
Compressor:	KWLA-016E-TAC-100
Compressor LRA - Low:	
Compressor LRA - High:	50.0
Compressor LRA -	
Compressor RLA:	6.6
Elect Application	1
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	
Fan Motor Quantity:	1.00

Water- Cooled Unit Performance

Release Date:	25-Apr-2002	Return Gas Temp. (°F):	65
Compressor:	KWLA-016E-TAC-100 x 1	Subcooling (°F):	5
Performance No:	3655	Condenser Water Inlet Temp.(°F)	85.0
		Water Temp Diff.(°F)	10

105°F Condensing Temperature			
<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond Water</u> <u>(gal/min)</u>	<u>(psi)</u>
-40	3,450	1.3	0.0
-35	4,200	1.5	0.0
-30	5,020	1.7	0.0
-25	5,920	1.9	0.0
-20	6,900	2.2	0.0
-15	7,960	2.5	0.0
-10	9,130	2.7	0.0
-5	10,410	3.0	0.0
0	11,800	3.3	0.0