

# M4PH-0025-IAA-111

HFC, R-404A, 60Hz, 1- Phase, 115 V



**Availability :** Standard US Wholesaler

## Mechanical

Unit Height (in):	10.5
Unit Length (in):	19.9
Unit Width (in):	11.0
Ship Weight (lbs):	41.0
Condensor Type:	
CopeVap Water Storage:	79
Liquid Connection Size (in)/Type:	1/4 S
Suction Connection Size (in)/Type:	3/8 S
Discharge Line Size(in):	0.250
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	12

## Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	10.7
Compressor:	ASE19C3E-IAA-103
Compressor LRA - Low:	
Compressor LRA - High:	34.6
Compressor LRA - Half winding:	
Compressor RLA:	8.0
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
Amps Per Motor:	0.36
Fan Motor Quantity:	1

## Air - Cooled Unit Performance

Release Date:	07-Feb-2001	Return Gas Temp. (°F):	65
Compressor:	ASE19C3E-IAA-103 x 1	Subcooling (°F):	5
Performance No:	3381	Air Flow Rate (CFM)	220

### 90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
0	1,600	108.4	18.4	3.7
5	1,730	110.5	20.5	3.8
10	1,890	112.8	22.8	3.9
15	2,060	115.2	25.2	4.0
20	2,230	117.7	27.7	4.1
25	2,430	120.3	30.4	4.3
30	2,620	123.0	33.0	4.3
35	2,820	125.9	35.9	4.4
40	3,030	128.8	38.8	4.5
45	3,270	132.0	42.0	4.6