

FGAH-A201-CFV-020

HFC, R-407C, 60Hz, 1- Phase, 208/230 V



Availability : **Obsolete**

Mechanical

Unit Height (in):	19.0
Unit Length (in):	25.2
Unit Width (in):	34.0
Ship Weight (lbs):	189.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	0.375
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	
Oil Recharge Amount (oz):	

Electrical

Max Fuse Size:	30
Min Circuit Ampacity:	19.2
Compressor:	CR24KQE-PFV-226TN
Compressor LRA - Low:	
Compressor LRA - High:	
Compressor LRA - Half winding:	
Compressor RLA:	
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	0.6
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	11-Sep-2009	Return Gas Temp. (°F):	65
Compressor:	CR24KQE-PFV-226TN x 1	Subcooling (°F):	5
Performance No:	7931	Air Flow Rate (CFM)	1680

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
0	6,940	102.7	12.7	4.9
5	8,350	104.5	14.5	5.5
10	9,790	106.4	16.4	6.1
15	11,300	108.4	18.4	6.6
20	12,900	110.4	20.4	7.2
25	14,500	112.5	22.5	7.7
30	16,200	114.6	24.6	8.3
35	18,000	116.8	26.8	8.8
40	19,900	119.0	29.0	9.3
45	21,900	121.4	31.4	9.8