



SLEEVE IS SHOWN INSTALLED

### THERMAL CHARACTERISTICS

- R-value of 4.2 when measured per ASTM C518 at 75°F mean temperature based on insulating same duct size.
- 1.25 inch thick, 0.75 PCF density glass fiber insulation has a C factor of 0.23
- Formaldehyde free insulation

### VAPOR BARRIER

- This metalized vapor barrier is constructed using fiberglass scrim which provides an outstanding combination of strength and tear resistance.
- Perm rating of 0.04 perms when measured per ASTM E96, Method A.

### SURFACE BURNING CHARACTERISTICS

- Flame Spread: Less than 25
- Smoke Developed: Less than 50

### SIZE AVAILABILITY

- Standard length: 5 feet
- Diameters offered: 4" - 10", 12", 14" & 16"
- One starter cone included in each carton

### APPROVALS

- Listed by Underwriter's Laboratories, Inc. as classified "Pipe and Equipment Covering - Materials."

JOB NAME: _____	SUBMITTED BY: _____	DATE: 7/17/2014	SD-5010
LOCATION: _____	<b>F204</b> Insulated Sleeve Metalized Vapor Barrier		
ARCHITECT: _____			
ENGINEER: _____			
CONTRACTOR: _____			