

Protecting Indoor

ERUS Air and Surfaces™

THE TECHNOLOGY

The Aerus® Mobile is a device intended for the reduction of contaminants in the ambient air in smaller indoor and personal spaces. Ideal for travel, work stations, small offices, and vehicles. Patented ActivePure Technology is an advanced surface and air purification technology.

ActivePure Technology does not replace the need to follow public health guidelines and should be used as complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens¹:

- · SARS-CoV-2
- Staphylococcus Aureus
- Aspergillus niger endospores
- H1N1 Influenza
- H5N8 Influenza
- MRSA
- Bacillus globigii •
- MS2 Bacteriophage
- Staphylococcus epidermidis
- PhiX-174

- Erwinia Herbicola
- Listeria monocytogenes
- Murine Norovirus
- E. coli
- · Candida auris
- Botrytis cinerea
- Sclerotinia sclerotiorum
- Legionella pneumophila
- · Aspergillus versicolor
- · Clostridium difficile
- · Salmonella enterica

THE BENEFITS

The Aerus Mobile lets you bring our proprietary ActivePure Technology with you on the go, to help reduce airborne contaminants, allergens, and odors. Multiple settings let you customize and optimize its usage for multiple environments ranging from a car, hotel room, small office, or camper.

- Touch sensitive settings to provide ease of operation and function
- Freshens air without the use of ozone

- · Uses a UVC light and ActivePure screen matrix to reduce contaminants in the air
- · Base is designed with multiple mounting options
- · Wire Stand allows for independent use from the base and various options to set or hang the unit
- · Comes with both a 12 volt DC car adapter and a 100 240 volt 50/60 Hz AC adapter with interchangeable plugs



¹ View test results at Aerusonline.com/Scientific-Proof







Inducted into the 2017 Space Technology Hall of Fame by the Space Foundation

Aerusonline.com



AERUS MOBILE

SPECIFICATIONS

Product Information	50111 Model: A1018D Meets California ozone emissions limit. CARB Certified	
Technology Included	ActivePure® Technology	
Electrical	12 Volt DC 100 - 240 VAC 50/60Hz with adapter Power Usage: 12 Volts, 10.7 Watts Max Conforms to UL STD 867	
Mechanical	Fuse: 2 Amp Buss type (12 Volt DC) Auto adapter only 3-speed fan	
Weight & Dimensions	8 ounces (0.22 kg) 3.625″ W x 6″ H x 1.0″ D (w/o base) (9.21 cm x 15.25 cm x 2.54 cm)	
Operating Temperature	45°F - 100°F (7°C - 38°C)	
Coverage ¹	Up to 50 sq. ft. (4.6 m²) for single occupant use. Not for use in medical or health care environments. ¹ Dependent on occupancy of the space	
Warranty	Limited 1 Year Warranty	

A ACTIVEPURE. TECHAN		Contact Name:
A HOLOGY POWER CONTRACT	<u></u>	Email:
A PCTIVEPURE TECHNO	•••	Phone Number:

1. Assumes 8 foot ceilings. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, other layers of protection.