



PURE CLOUD

Features ActivePure® Technology proven to reduce viruses, bacteria, and other pathogens (full list of tested pathogens available below in “The Proof”)

THE TECHNOLOGY

The Aerus® Pure Cloud provides ActivePure Technology in the form of a 2'x2' ceiling tile for situations when a portable unit cannot fit in the room. Patented ActivePure Technology is an advanced surface and air purification technology. It has been proven to reduce over 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in “The Proof” section below).

ActivePure Technology does not replace the need to follow public health guidelines and should be used as a complementary technology.

THE PROOF


In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens¹:

- SARS-CoV-2
- Staphylococcus Aureus
- Aspergillus niger endospores
- H1N1 Influenza
- H5N8 Influenza
- MRSA
- Bacillus globigii
- MS2 Bacteriophage
- Staphylococcus epidermidis
- PhiX-174
- Erwinia Herbicola
- Listeria monocytogenes
- Murine Norovirus
- E. coli
- Candida auris
- Botrytis cinerea
- Sclerotinia sclerotiorum
- Legionella pneumophila
- Aspergillus versicolor
- Clostridium difficile
- Salmonella enterica

THE BENEFITS

The Aerus Pure Cloud provides surface decontamination and air purification 24/7. It is a proactive and effective solution for your home or business.

- Over a decade of testing, patented ActivePure® Technology has been proven to reduce over 99.9% of many common airborne and surface contaminants including viruses, bacteria, mold, fungi, VOC gases, smoke, allergens, and odors (full list of tested pathogens available in “The Proof” section)¹
- Provides 24/7 surface decontamination & air purification
- Discreet and easy installation



Inducted into the 2017 Space Technology Hall of Fame by the Space Foundation

Assembled in USA



¹ View test results at Activepure.com/scientific-proof



PURE CLOUD

SPECIFICATIONS

Product Information	120V: 9960023 Model: A1021C Model A1021C Meets California ozone emissions limit. CARB Certified. 230V: 9960026 Model: A1021B
Technology Included	ActivePure® Technology
Electrical	110-120V 60Hz .75A (90W) / 220V - 240V 50Hz 0.3 Amp Conforms to UL STD 867
Mechanical	100CFM (Fan) 2.83 m ³ /min, impedance protected motor, UV-C bulb, 26 watts, safety power switch
Weight & Dimensions	12 lbs (5.44 kg) 24" H x 24" W x 5" D (60.96 cm H x 60.96 cm W x 12.7 cm D)
Operating Temperature	34°F – 200°F (1.1°C – 93°C)
Coverage ¹	Up to 2,500 sq. ft. (232 m ²) Maximum.
Warranty	Limited 3 year warranty



Contact Name: _____



Email: _____



Phone Number: _____

1. Assumes 8 foot ceilings. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, and other layers of protection.