

ZR61K3E-TF5

HFC, R-407C, 60 Hz, 3 - Phase, 200/230 V [. Also Available with Variable Frequency Drives](#)

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance			Mechanical	
Evaporator Temp. (°F)	45.00	45	Displacement (in ³ /Rev):	5.04
Condensing Temp. (°F)	130.00	100	Displacement (ft ³ /Hr):	
Return Gas Temp. (°F)	65.00	65	Overall Length (in):	9.69
Liquid Temp. (°F)	115.00	85	Overall Width (in):	9.69
Capacity (BTU/hr)	58700	70800	Overall Height (in):	17.24
Power (W):	5470	3620	Mounting Length (in):	7.50
Current (Amps):	16.4	12.2	Mounting Width (in):	7.50
EER(BTU/Wh):	10.75	19.55	Mounting Height (in):	17.99
Mass Flow (lbs/hr):	848	874	Suction Size (in),Type:	7 / 8 Stub
Sound Data @			Discharge Size (in),Type:	1 / 2 Stub
Sound Power (dBA):	74 Avg	79 Max	Initial Oil Charge (oz):	66
Vibration mils(peak-peak):	2.0 Avg	3.0 Max	Oil Recharge (oz):	62
Record Date:	2014-08-07		Oil Type:	3MA
			Net Weight (lbs):	84.0
			Internal Free Volume (in ³):	257.0
			Horse Power:	5.0
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical		Capacitors					
LRA High* (Amps):	137.0	Type	Part No	Low MFD	High MFD	Volts	User Description
LRA Low*(Amps):		No data available in table					
LRA Half Winding (Amps):							
MCC (Amps):	27						
Max Operating Current (Amps):	19.4						
RLA, MCC/1.4(use for contactor selection)(Amps):	19.3						
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	17.3						
RPM:	3500						
Box IP :	21						
UL File No:	SA-2337						
UL File Date:	2014-03-21						

*Low and High refer to the low and high nominal voltage ranges for

which the motor is approved.

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-22 HCFC	200/220	3	50	Air Conditioning
R-22 HCFC	200/230	3	60	Air Conditioning
R-407C HFC	200/220	3	50	Air Conditioning