

DAX – Multi-Speed Upflow Air Handler 7½ & 10 Tons



*Complete warranty details available from your local distributor or manufacturer’s representative or at www.daikincomfort.com.

The Daikin DAX Multi-Speed, Multi-Position Air Handlers are suitable for upflow or left side horizontal installations to accompany your 7½ and 10-ton split-system units. These unit feature a fully insulated fiberglass blanket for quiet, efficient operation.



DESIGNED FOR EXCEPTIONAL DURABILITY, ENERGY EFFICIENCY, AND OUTSTANDING PERFORMANCE.

- » Circuited for use with one (1) 7½-ton or one (1) 10-ton cooling-only or heat pump system. Also circuited for use with two (2) 4-ton or two (2) 5-ton cooling-only units
- » Copper tube/aluminum fin coils
- » TXV control; 7½-ton unit has one (2) thermal expansion valves; 10-ton unit has two (2) thermal expansion valves
- » Draw-thru centrifugal blower is direct-driven for quiet, efficient operation
- » Heavy-gauge, reinforced, galvanized-steel cabinet
- » Fully insulated with fiberglass blanket
- » Horizontal and vertical condensate pans
- » Built-in filter rack (2" filter included)
- » Entry on top of panel for both low and high voltages
- » Removable access panels make servicing of unit faster and easier

Model	Nominal Cooling (BTU/h)	Electric Heat (kW)	CFM @ 0.3" ESP	Voltage-Phase Phase	Dimensions			Service Valve		Ship Weight (lbs)
					W"	D"	H"	Liquid"	Suction"	
DAX09043	90,000	15, 20, 30	3,000	208/240-3	48½	24	60½	¾"	1½"	430
DAX09044	90,000	15, 20, 30	3,000	460-3	48½	24	60½	¾"	1½"	430
DAX12043	120,000	15, 20, 30	4,000	208/240-3	48½	24	60½	¾"	1½"	430
DAX12044	120,000	15, 20, 30	4,000	460-3	48½	24	60½	¾"	1½"	430

*For two refrigerant lines

Daikin North America LLC reserves the right to discontinue or change at any time specifications or designs without notice or without incurring obligations.