



A CSW Industrials Company

PRODUCT DATA SHEET

ZIPP™

Quick drying safe degreaser

Description

ZIPP™ is a quick drying safe solvent degreaser that instantly removes grease, oil, waxes, tar, gums, grime, dirt, carbon, greasy stains, bilge slime and similar soils from most hard surfaces. It may be used on oil burner parts, compressors, refrigeration units, greasy fan blades, strainers, engines, stoves, relay contact points and electrical equipment. **It will not short out electrical equipment.**



Application

ZIPP™ may be used to degrease and clean oil burner parts, compressors, refrigeration units, strainers, engines, stoves, fan blades, relay contact parts and electrical equipment.

Characteristics | Features

- Non-flammable
- Non-conductive
- Excellent cleaner/degreaser
- Fast Drying
- Leaves no residue

Packaging

Code	Size	Qty per Case	Lbs. per Case	Cubic Ft per Case
88442	14 ounce aerosol	12	14	0.52

Instructions

**READ ALL DIRECTIONS, SDS AND WARNINGS ON LABEL BEFORE USING
DO NOT USE ON PLASTICS WITHOUT TESTING FIRST**

- For best results, use only on cool surfaces. Shake can well.
- Thoroughly saturate part(s) to be cleaned.
- Spray on small parts with light oil or grease films and on contact points on relays, motors, thermostats, and in all electrical or mechanical equipment.
- For heavy grease and grime deposits allow 5 minutes soaking time. Some agitation with brush or rag is very helpful
- Allow to air dry

For additional technical information, call Toll Free 1-800-231-3345

Precautions

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

KEEP OUT OF REACH OF CHILDREN.

For additional information, refer to Safety Data Sheet.

Specifications

Wt/Gal @ 77°F	11.99 lbs/ gal
Flash Point SETA CC	None
Color	Clear liquid
Shelf Life	2 years minimum

NOT FOR SALE IN CALIFORNIA

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

Limited Warranty

For more information on our product warranty, visit RectorSeal.com

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive, Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

PO Box 5266, Brendale, Qld 4500, Australia • 1300 772 878 • rectorseal.com.au

3255 Wyandotte St. East, Windsor, ON N8Y 1E9, Canada • 519-966-4901

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensors and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2023 RectorSeal. All rights reserved. R50192-1023