



# Safety Data Sheet

## BOSS® 326 Hi-Temp Red Silicone

### Section 1. Identification

Product Identifier	BOSS® 326 Hi-Temp Red Silicone		
Synonyms	32612; 32610; 32603; 32650; 32620; 01000RD72; 01700RD48; 01300RD05; 01000RD12; 01048RD01		
Manufacturer Stock Numbers	01000RD72; 01700RD48; 01300RD05; 01000RD12; 01048RD01		
Recommended use	Refer to Technical Information		
Uses advised against	Refer to Technical Information		
Manufacturer Contact			
Address	Soudal Accumetric 350 Ring Road Elizabethtown, KY, 42701 USA		
	Phone	Emergency Phone	Fax
	(270) 769-3385	(800) 424-9300 CHEMTREC	(270) 765-2412

### Section 2. Hazards Identification

Classification	N/A
Signal Word	
Pictogram	
Hazard Statements	N/A
Precautionary Statements	
Response	N/A
Prevention	Use only outdoors or in a well-ventilated area.

Storage	N/A
Disposal	N/A

Ingredients of unknown toxicity 0%

Hazards not Otherwise Classified

GHS Classification Not a hazardous substance or mixture.

GHS Label Element Not a hazardous substance or mixture.

Other hazards None known

## Section 3. Ingredients

CAS	Ingredient Name	Weight %
Mixture	Contains no hazardous ingredients according to GHS	100 %

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First-Aid Measures

Description of first aid measures

General advice:

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation

Move person to fresh air; if effects occur, consult a physician.

Skin contact

Wash off with plenty of water.

Eye contact

Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion

No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician

No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

## Section 5. Fire Fighting Measures

Suitable Extinguishing Media	Water spray, Alcohol-resistant foam, Carbon dioxide (CO <sub>2</sub> ), Dry chemical
Unsuitable Extinguishing Media	None known
Special hazards arising from the substance or mixture	Hazardous combustion products Carbon oxides Silicon oxides  Unusual Fire and Explosion Hazards Exposure to combustion products may be a hazard to health.
Advice for firefighters	Fire Fighting Procedures Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.  Special protective equipment for firefighters Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

## Section 6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Follow safe handling advice and personal protective equipment recommendations.
Environmental precautions	Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. See sections: 7, 8, 11, 12 and 13.

## Section 7. Handling and Storage

Precautions for safe handling	Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Conditions for safe storage	Keep in properly labeled containers. Store in accordance with the particular national regulations.  Do not store with the following product types: Strong oxidizing agents.

Unsuitable materials for containers:  
None known.

## Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Contains no hazardous ingredients according to GHS	N/A	N/A	N/A
Personal Protective Equipment Control parameters	Goggles  If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.			
Exposure controls	Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.  Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.			
Individual protection measures	Eye/face protection Use safety glasses (with side shields).  Skin protection Hand protection Chemical protective gloves should not be needed when handling this material. Consistent with general hygienic practice for any material, skin contact should be minimized.  Other protection No precautions other than clean body-covering clothing should be needed.  Respiratory protection Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures without sufficient ventilation, use an approved air-purifying respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge.			

## Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Red
Odor	Acetic acid
Odor Threshold	No data available
Solubility	No data available
Partition coefficient Water/n-octanol	No data available
VOC%	23 g/L
Viscosity	Not applicable
Specific Gravity	1.007
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	> 100C
FP Method	Closed cup
pH	Not applicable
Melting Point	No data available
Boiling Point	Not applicable
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Not applicable
Flammability	Not classified as a flammability hazard
Decomposition Temperature	No data available
Auto-ignition Temperature	No data available
Vapor Pressure	Not applicable
Vapor Density	No data available

### Note

The above information is not intended for use in preparing product specifications. Contact Soudal Accumetric before writing specifications.

## Section 10. Stability and Reactivity

Reactivity	Not classified as a reactivity hazard.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	Can react with strong oxidizing agents. When heated to temperatures above 150 °C (300 °F) in the presence of air, trace quantities of formaldehyde may be released. Adequate ventilation is required.
Conditions to avoid	None known
Incompatible materials	Oxidizing agents
Hazardous decomposition products	Formaldehyde

## Section 11. Toxicological Information

Acute toxicity	<p>Toxicological information appears in this section when such data is available.</p> <p>Acute oral toxicity Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.</p> <p>As product: Single dose oral LD50 has not been determined.</p> <p>Based on information for component(s): LD50, Rat, &gt; 5,000 mg/kg Estimated.</p> <p>Acute dermal toxicity Prolonged skin contact is unlikely to result in absorption of harmful amounts.</p> <p>As product: The dermal LD50 has not been determined.</p> <p>Based on information for component(s): LD50, Rabbit, &gt; 2,000 mg/kg Estimated.</p> <p>Acute inhalation toxicity Brief exposure (minutes) is not likely to cause adverse effects. Vapor from heated material may cause respiratory irritation.</p> <p>As product: The LC50 has not been determined.</p>
Skin corrosion/irritation	Prolonged exposure not likely to cause significant skin irritation.
Serious eye damage/eye irritation	May cause slight temporary eye irritation. Corneal injury is unlikely. May cause mild eye discomfort.
Sensitization	<p>For skin sensitization: Contains component(s) which did not cause allergic skin sensitization in guinea pigs.</p> <p>For respiratory sensitization: No relevant information found.</p>
Specific Target Organ Systemic Toxicity	Single Exposure Evaluation of available data suggests that this material is not an STOT-SE toxicant.

#### Repeated Exposure

For the major component(s): Based on available data, repeated exposures are not anticipated to cause additional significant adverse effects.

Contains an additional component(s) that is/are encapsulated in the product and are not expected to be released under normal processing conditions or foreseeable emergency.

#### Carcinogenicity

For this family of materials: Did not cause cancer in long-term animal studies which used routes of exposure considered relevant to industrial handling. Positive results have been reported in other studies using routes of exposure not relevant to industrial handling.

#### Teratogenicity

Contains component(s) which did not cause birth defects or any other fetal effects in lab animals.

#### Reproductive toxicity

Contains component(s) which did not interfere with reproduction in animal studies.

#### Mutagenicity

Contains a component(s) which were negative in in vitro genetic toxicity studies. Contains component(s) which were negative in animal genetic toxicity studies.

#### Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

## Section 12. Ecological Information

Ecotoxicological information appears in this section when such data is available.

#### Toxicity

No data available.

#### Persistence and degradability

No data available.

#### Bioaccumulative potential

No data available.

#### Mobility in soil

No data available.

## Section 13. Disposal

#### Disposal methods

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

#### Treatment and disposal methods of used

Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with

packaging

applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

## Section 14. Transport Information

UN Number N/A  
UN Proper Shipping Name Not regulated for transport  
DOT Classification Not regulated for transport  
Packing Group Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

## Section 15. Regulatory Information

SARA Sections 311 and 312 No SARA Hazards

SARA Section 313 This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

CERCLA Section 103 Calculated RQ exceeds reasonably attainable upper limit.  
Components  
Acetic acid (64-19-7) 5000 lbs RQ

Acetic anhydride (108-24-7) 5000 lbs RQ

Pennsylvania Right To Know The following chemicals are listed because of the additional requirements of Pennsylvania law:  
Polydimethylsiloxane hydroxy-terminated (70131-67-8)  
Silicon dioxide (7631-86-9)

United States TSCA Inventory (TSCA) All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

California Prop 65 Clear  
This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Black  
WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Other Colors  
WARNING: This product can expose you to chemicals including Titanium



## Section 16. Other Information

Revision Date 5/31/2018

HMIS and NFPA Rating  
HMIS  
Health: 0  
Fire: 1  
Reactivity: 0

NFPA  
Health: 0  
Fire: 1  
Reactivity: 0

Hazard Scale:  
0 = Minimal  
1 = Slight  
2 = Moderate  
3 = Serious  
4 = Severe  
\* = Chronic hazard

### Disclaimer

The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.



# Safety Data Sheet

## BOSS® 326 Hi-Temp Red Silicone Sealant Pressure Can


### Section 1. Identification

Product Identifier	BOSS® 326 Hi-Temp Red Silicone Sealant Pressure Can		
Synonyms	32608; 01677RD10		
Manufacturer Stock Numbers	N/A		
Recommended use	Refer to Technical Information		
Uses advised against	Refer to Technical Information		
Manufacturer Contact Address	Soudal Accumetric 350 Ring Road Elizabethtown, KY, 42701 USA		
	Phone	Emergency Phone	Fax
	(270) 769-3385	(800) 424-9300 CHEMTREC	(270) 765-2412

### Section 2. Hazards Identification

Classification	EYE DAMAGE/IRRITATION - Category 2A GASES UNDER PRESSURE - Liquefied gas SKIN CORROSION/IRRITATION - Category 2
Signal Word	Warning

## Pictogram



## Hazard Statements

Causes serious eye irritation  
Causes skin irritation  
Contains gas under pressure; may explode if heated

## Precautionary Statements

### Response

If eye irritation persists: Get medical advice/attention.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If medical advice is needed, have product container or label at hand.  
If on skin: Wash with plenty of soap and water.  
If skin irritation occurs: Get medical advice/attention.  
Take off contaminated clothing and wash it before reuse.

### Prevention

Wash thoroughly after handling.  
Wear eye protection/face protection.  
Wear protective gloves.

### Storage

Protect from sunlight. Store in a well-ventilated place.

### Disposal

Dispose of contents/container in accordance with local, regional, national and international regulations.

Ingredients of unknown toxicity

0%

Hazards not Otherwise Classified

Additional Information

None known

## Section 3. Ingredients

CAS	Ingredient Name	Weight %
7631-86-9	Amorphous silica	6% - 9%
75-37-6	Difluoroethane (propellant)	1% - 5%

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First-Aid Measures

Description of necessary first aid measures

Eye Contact  
Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention.

### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

### Skin Contact

Flush contaminated skin with plenty of water. Continue to rinse for at least 20 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

### Ingestion

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Eye contact

Causes serious eye irritation.

### Inhalation

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

### Ingestion

Irritating to mouth, throat and stomach.

### Skin contact

Causes skin irritation.

### Eye contact

Adverse symptoms may include the following:  
pain or irritation, watering, redness

### Inhalation

No known significant effects or critical hazards.

### Skin contact

Adverse symptoms may include the following:  
irritation, redness

### Ingestion

Potential acute health effects

Over-exposure signs/symptoms

No known significant effects or critical hazards.

Indication of immediate medical attention and special treatment needed

Notes to physician

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

No specific treatment.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Note

See toxicological information (Section 11).

## Section 5. Fire Fighting Measures

Suitable Extinguishing Media

Use an extinguishing agent suitable for the surrounding fire.

Unsuitable Extinguishing Media

None known

Specific hazards arising from the chemical

No specific fire or explosion hazard.

Hazardous thermal decomposition products

Decomposition products may include the following materials: carbon dioxide, carbon monoxide, halogenated compounds, carbonyl halides, metal oxide/oxides

Special protective actions for fire fighters

No special precaution is required.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel:

No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions:

Avoid dispersal of spilled material and runoff and contact with soil, waterways,

drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

Move containers from spill area. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Do not dry sweep. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and Storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits

Ingredient Name	ACGIH TLV	OSHA PEL	STEL
Amorphous silica	10 mg/m <sup>3</sup>	6 mg/m <sup>3</sup>	Not Est.
Difluoroethane (propellant)	Not established	Not established	N/A

Personal Protective Equipment

Goggles, Gloves

Appropriate engineering controls

Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

## Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or gases. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

## Skin protection

### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

### Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## Respiratory protection

Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Red
Odor	Acetic acid
Odor Threshold	No data available
Solubility	No data available
Partition coefficient Water/n-octanol	No data available
VOC%	23 g/L
Viscosity	Not applicable
Specific Gravity	1.007





Information on toxicological effects

Acute toxicity:  
There is no data available.

Irritation/corrosion:  
There is no data available.

Sensitization:  
There is no data available.

Mutagenicity:  
There is no data available.

Carcinogenicity:  
There is no data available.

Reproductive toxicity:  
There is no data available.

Teratogenicity:  
There is no data available.

Specific target organ toxicity (single exposure):  
There is no data available.

Specific target organ toxicity (repeated exposure):  
There is no data available.

Aspiration hazard:  
There is no data available.

Information on the likely routes of exposure

Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Eye contact  
Causes serious eye irritation

Inhalation  
Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Skin contact  
Causes skin irritation.

Ingestion  
Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact  
Adverse symptoms may include the following:  
pain or irritation, watering, redness

Inhalation  
No known significant effects or critical hazards.

Skin contact

Adverse symptoms may include the following:  
irritation, redness

Ingestion  
No known significant effects or critical hazards.

Delayed and immediate effects and also chronic effects from short and long term

Short term exposure  
Potential immediate effects: No known significant effects or critical hazards.  
Potential delayed effects: No known significant effects or critical hazards.

Potential chronic health effects

Long term exposure  
Potential immediate effects: No known significant effects or critical hazards.  
Potential delayed effects: No known significant effects or critical hazards.

General:  
No known significant effects or critical hazards.

Carcinogenicity:  
No known significant effects or critical hazards.

Mutagenicity:  
No known significant effects or critical hazards.

Teratogenicity:  
No known significant effects or critical hazards.

Developmental effects:  
No known significant effects or critical hazards.

Fertility effects:  
No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates: There is no data available.

## Section 12. Ecological Information

Toxicity	There is no data available.
Persistence and degradability	There is no data available.
Bioaccumulative potential	There is no data available.
Other adverse effects	No known significant effects or critical hazards.

## Section 13. Disposal

Disposal methods	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the
------------------	---

requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

## Section 14. Transport Information

UN Number	1950
UN Proper Shipping Name	Aerosols, flammable (each not exceeding 1 L capacity) (1,1-Difluoroethane)
DOT Classification	Transport hazard class: 2.1
Packing Group	-
Special precautions for user:	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not available

## Section 15. Regulatory Information

United States inventory (TSCA 8b)	All components are listed or exempted.
Clean Air Act (CAA)	Section 112 Regulated Flammable Substances 1,1-Difluoroethane  Section 112 (b) Hazardous Air Pollutants (HAPs) Not listed  Section 602 Class I Substances Not listed  Section 602 Class II Substances Not listed
SARA	SARA 302/304 Composition/information on ingredients No products were found.  SARA 304 RQ Not applicable  SARA 311/312 Classification Sudden release of pressure Immediate (acute) health hazard

## State Regulations

### Massachusetts

The following components are listed: Silicon dioxide; 1,1-Difluoroethane

### New York

None of the components are listed.

### New Jersey

The following components are listed: 1,1-Difluoroethane

### Pennsylvania

The following components are listed: Silicon dioxide

## Chemical Weapons Convention List

### Schedule I

Not listed

### Schedule II

Not listed

### Schedule III

Not listed

## California Prop 65

### Clear

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### Black

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### Other Colors

WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## Section 16. Other Information

### Revision Date

5/31/2018

### Disclaimer

The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.